

YUR.POWER

A-M204

Monocrystalline Solar Panels



Specifications

• Panel Type	204 Wp Monocrystalline silicon photovoltaic module
• Maximum Power (Pmax)	204 W
• Voltage @ Pmax (Vpm)	26,94 V
• Current @ Pmax (Ipm)	7,58 A
• Open Circuit Voltage (Voc)	32,98 V
• Short Circuit Current (Isc)	8,15 A
• Output Tolerance	± 3 %
• Maximum System Voltage	1000 Vdc
• Series fuse rating	10 A
• Application	DC 24V system
• Efficiency of module	13,9 %
• Temperature Coefficients of Pmax (%)	-0,37 % /°C
• Temperature Coefficients of Voc (%)	-0,34 % /°C
• Temperature Coefficients of Isc (%)	+0,09 % /°C
• Operating Temperature	-40 to +85 °C
• Storage Temperature	-40 to +85 °C
• System Cell	6" Monocrystalline silicon
• No. of cells & connections	54 pcs in series (6x9)
• Module Size (WxLxH)	1474 x 995 x 50 mm
• Weight	Approximately 18,6 Kg
• Packing configuration	Horizontal
• Size of carton	1531 x 1071 x 955 mm
• Pallet quantity	18 pcs / pallet
• Container Load (20ft/40ft)	14 pallets / 28 pallets

Construction

• Front	High transmission low-iron tempered glass (3.2 mm)
• Back	PVF / PET / PVF
• Encapsulates	EVA
• Junction Box Type	IP65, waterproof
• Bypass Diodes	3 diodes to avoid power decreasing by shade
• Output cable	4 mm ² cable with polarized waterproof tyco connectors (Negative 900 mm, Positive 900 mm)
• Frame (Material, Corners, etc)	Clear anodized aluminium, AL6063-T5
• Certification	IEC 61215 : 2005 + EN 61730-1 / EN 61730-2 : 2007

*measured at STC (Standard Test Condition; 1000 W/m² irradiance, AM 1.5G and 25 °C)



Warranty Notice: 5 years on materials. 10 years of 90 % output, 25 years of 80 % output.

EAN : TBA

Yuraku Pte Ltd
 11 Collyer Quay,
 #10-04 The Arcade, Singapore 049 317
 Tel: +65 6238 2158
 Fax: +65 6238 0076
 Website: www.yuraku.com.sg

Yuraku S.r.l
 Via Fratelli Rosselli 3/2
 20019 Settimo Milanese (Milano) Italy
 Tel: +39 02 3351 4444
 Fax: +39 02 3359 0580
 Website: www.yuraku.it

Yuraku, SL
 C/Florida Nº 1 (nave 4) Pol. Ind. Villapark
 28670 Villaviciosa de Odón (Madrid) España
 Tel: +34 91 6657 423
 Fax: +34 91 6166 324
 Website: www.yuraku.es

create >> excite >> inspire

Terms and Specifications are subjected to change without notice.
 ©2010 YURAKU PTE LTD