## ICD Monitor



## **Ambient Light Adaptation (Optional):**

Brightness level adjust automatically and continuously base on various different light conditions.



## **Product Life Extension:**

Optimize and extend product life cycle by enhancing efficiency.

## Visual Ergonomic:

IBT Technology provides comfort and tranquil visual sensation for your eyes.

Model		MW9A
LCD Panel	Туре	19.0" TFT Active Matrix LCD Display
	Viewing Angle *	H: 150°, V: 130° *
	Contrast Ratio *	500:1*
	Brightness *	300 cd/m <sup>2</sup> *
	Response Time *	8 ms *
	Display Colors	16.2M colors
	Max Resolution	1440 x 900 (WXGA+)
	Pixel Pitch	0.285mm (H) x 0.285mm (V)
Compatibility	PC	Up to 1440 x 900 @75Hz (Non-interlaced)
Connector	RGB Analog	D-sub 15-pins
	DVI *	DVI-D *
	Audio	Stereo Phone Jack
	Power	A/C Socket
Power	Voltage	100-240V, 50/60Hz (universal) via internal power supply
	Consumption	Active < 50Watt Max
Internal Speaker		Speaker x 2 (Stereo) *
Dimensions	Physical	462mm (W) x 385mm (H) x 180mm (D)
Net Weight		4.0Kg ± 1
DDC		DDC2B Compliant
Power Management		VESA DPMS
Others	Security	Kensington Lock Support 🔒
Regulation		CE, FCC, UL

Notice \* LCD Panel, DVI and Speaker functions are optional

